



### Principal

Gama de producto	Easy9
Tipo de producto o componente	Residual current circuit breaker (RCCB)
Device short name	Easy9 RCCB
Poles description	2P
Neutral position	Left
[In] rated current	40 A
Tipo de red	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC
Rated breaking and making capacity	500 A
Rated conditional short-circuit current	With Easy9 MCB: 6000 A 40 A

### Complementos

Device location in system	Outgoer
Frecuencia de red	50/60 Hz
[Ue] tensión de funcionamiento nominal	230 V AC 50/60 Hz
Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	440 V AC
[Uimp] rated impulse withstand voltage	4 kV
Contact position indicator	Yes
Control type	Toggle
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
9 mm pitches	4
Altura	82 mm
Anchura	36 mm
Profundidad	72 mm
Colour	Grey RAL 7035
Mechanical durability	5000 Ciclos
Durabilidad eléctrica	AC: 2000 cycles 230 V AC 50/60 Hz
Conexiones - terminales	Tunnel type terminal top or bottom 1...35 mm <sup>2</sup> rigid Tunnel type terminal top or bottom 1...25 mm <sup>2</sup> flexible
Tightening torque	3.5 N.m (top or bottom)

### Ambiente

Normas	IEC 61008-1
Certificaciones de producto	CE
IP degree of protection	IP20
Pollution degree	2 conforming to IEC 61008-1
Tropicalisation	2
Relative humidity	95 % ( 55 °C )

Temperatura ambiente de trabajo	-5...60 °C
Temperatura ambiente de almacenamiento	-40...85 °C

### Oferta sustentable

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1650 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold