



Principal

Gama	EasyPact
Product name	EasyPact TVS
Tipo de producto o componente	Contactador
Device short name	LC1E
Contactador application	Resistive load Motor control
Categoría de empleo	AC-1 AC-3
Poles description	3P
Pole contact composition	3 NO
[Ue] tensión de funcionamiento nominal	<= 690 V AC 50/60 Hz para power circuit
[Ie] intensidad de funcionamiento nominal	25 A (<= 60 °C) AC AC-3for power circuit <= 440 V 36 A (<= 60 °C) AC AC-1for power circuit <= 440 V
Motor power kW	15 kW at 660...690 V 11 kW at 380...400 V 11 kW at 415 V 11 kW at 440 V 5.5 kW a 220...230 V AC 50/60 Hz 15 kW at 500 V
Control circuit type	AC 50 Hz
[Uc] control circuit voltage	220 V AC 50 Hz
Altura	74 mm
Anchura	45 mm
Profundidad	85 mm
Peso del producto	0.36 kg
Colour	Grey RAL 7011

Complementos


Auxiliary contact composition	1 NO
[Uimp] rated impulse withstand voltage	6 kV (coil not connected to the power circuit) IEC 60947
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Irms rated making capacity	250 A - 440 V ACfor power circuit conforming to IEC 60947-4-1
Rated breaking capacity	200 kA at 440 Vfor power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	240 kA at <= 40 °C - 10 s for power circuit 120 kA at <= 40 °C - 60 s for power circuit 50 kA at <= 40 °C - 600 s for power circuit
Associated fuse rating	10 A gG <= 690 V type 1 control circuit IEC 60947-5-1 40 A gG <= 690 V type 1 power circuit
Average impedance	2.5 mOhm at 50 Hz Ith 36 Afor power circuit
Power dissipation per pole	3.2 W AC-1 1.6 W AC-3
Control circuit voltage limits	0.3...0.6 Uc at <= 55 °C drop-out 50 Hz 0.85...1.1 Uc at <= 55 °C operational 50 Hz
Operating time	12...22 ms on closing 4...19 ms on opening
Mechanical durability	10000000 Ciclos
Operating rate	1800 cyc/h at <= 60 °C

Inrush power in VA	95 VA at 20 °C (0.75) 60 Hz 95 VA at 20 °C (0.75) 50 Hz
Hold-in power consumption in VA	8.5 VA at 20 °C (0.3) 50 Hz 8.5 VA at 20 °C (0.3) 60 Hz
Heat dissipation	2...3 Wfor control circuit
Minimum switching current	5 mA control circuit
Minimum switching voltage	17 V control circuit
Non-overlap time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
Insulation resistance	> 10 MOhm control circuit
Durabilidad eléctrica	300000 cycles AC-3 350000 cycles AC-1
Mounting support	Plate DIN rail
Conexiones - terminales	Control circuit : screw clamp terminals - 1 flexible cable(s) 1...4 mm ² without cable end Control circuit : screw clamp terminals - 2 flexible cable(s) 1...4 mm ² without cable end Control circuit : screw clamp terminals - 1 flexible cable(s) 1...4 mm ² with cable end Control circuit : screw clamp terminals - 2 flexible cable(s) 1...2.5 mm ² with cable end Control circuit : screw clamp terminals - 1 solid cable(s) 1...4 mm ² without cable end Control circuit : screw clamp terminals - 2 solid cable(s) 1...4 mm ² without cable end Power circuit : screw clamp terminals - 1 solid cable(s) 1.5...6 mm ² without cable end Power circuit : screw clamp terminals - 2 solid cable(s) 1.5...6 mm ² without cable end Power circuit : screw clamp terminals - 1 flexible cable(s) 1...6 mm ² with cable end Power circuit : screw clamp terminals - 2 flexible cable(s) 1...4 mm ² with cable end
Tightening torque	1.5 N.mfor control circuit 1.5 N.mfor power circuit

Ambiente

Normas	IEC 60947-4-1 IEC 60947-5-1 IEC 60947-1
Certificaciones de producto	EAC
IP degree of protection	IP2x conforming to IEC 60529
Protective treatment	TH IEC 60068 3
Pollution degree	3
Temperatura ambiente de trabajo	5...55 °C
Temperatura ambiente de almacenamiento	-60...80 °C
Permissible ambient air temperature around the device	-20...70 °C at Uc
Operating altitude	3000 m without derating
Fire resistance	850 °C IEC 60695-2-1
Mechanical robustness	Vibrations contactor open 1.5 Gn, 5...300 Hz Vibrations contactor closed 3 Gn, 5...300 Hz Shocks contactor closed 10 Gn for 11 ms Shocks contactor open 6 Gn for 11 ms

Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1110 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Garantia contractual

Warranty period	18 months
-----------------	-----------
