



Main

Range	Miluz
Aesthetic name	Bossa
Product or component type	Switch

Complementary

Device presentation	Complete mechanism
Colour tint	Polar white (RAL 9003)
Type of packing	Flow-pack
Switch function	1-way + 2-way switch
Local signalling	Without pilot light
Marking	1 - L 1 - 2 - L
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC
Material	ABS (acrylonitrile butadiene-styrene): wiring device
Number of modules	2 modules
Fixing mode	By screws
Connections - terminals	Screw-clamp terminals
Cable cross section	4 Mm ²
AWG gauge	AWG 12
Height	111 Mm
Width	73 Mm
Depth	36 Mm
Embedding depth	26 Mm
Projecting depth	10 Mm




Environment

Standards	ABNT NBR NM 60.669
Product certifications	NOM/ANCE RETIE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	69.0 G
Package 1 Height	40.0 Mm
Package 1 width	115.0 Mm
Package 1 Length	77.0 Mm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	1589.0 G
Package 2 Height	15.8 Cm
Package 2 width	21.5 Cm
Package 2 Length	26.5 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Product Life Status :	Commercialised
-----------------------	----------------