


Product data sheet

Specifications



Triple Italian socket outlet, Miluz, 2P +E, 10A, 250V, white

S3B60480

Main

Range	Miluz
Product or component type	Socket-outlet Cover frame
Fixing mode	By screws

Complementary

Device presentation	Complete mechanism
Outlet standard description	With earthing contact
Outlet poles configuration	2P + E
Device mounting	Flush
Colour tint	White (RAL 9003)
Outlet standard	Italian
Type of packing	Flow-pack
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC
Material	ASA + PC: centre plate Thermoplastic ABS-UV stabilised: cover frame PS (polystyrene): fixing frame PC (polycarbonate): casing
Surface finish	Glossy
Number of modules	3 modules
Connections - terminals	Screw-clamp terminals
Number of cables	2
Cable cross section	1.5...2.5 mm²
Wire stripping length	11 mm
AWG gauge	AWG 14
Height	115.0 mm
Width	77.0 mm
Depth	30.5 mm
Embedding depth	22.0 mm
Projecting depth	8.5 mm

Environment

Standards	NCh 2027/1 NCh 2027/2
IP degree of protection	IP2x

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	92.874 g
Package 1 Height	3.055 cm
Package 1 width	9.5 cm
Package 1 Length	19.0 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	1.857 kg
Package 2 Height	21.5 cm
Package 2 width	15.8 cm
Package 2 Length	26.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)