



Main

Range	Miluz
Product or component type	Switch and socket-outlet
Device presentation	Complete mechanism
Outlet poles configuration	2P + E
Outlet standard	Italian
Colour tint	White (RAL 9003)
Type of packing	Flow-pack

Complementary

Switch function	1-way
[In] rated current	10 A wiring device
[Ue] rated operational voltage	250 V AC
Local signalling	Without
Material	Thermoplastic ABS-UV stabilised: cover frame ASA + PC: centre plate PC (polycarbonate): casing Thermoplastic ABS-UV stabilised: rocker PA66: casing PS (polystyrene): fixing frame
Number of modules	2 modules
Fixing mode	By screw
Connections - terminals	Screw-clamp terminals
Cable outer diameter	4.0 Mm 2.5 Mm
AWG gauge	AWG 12 AWG 14
Height	115.0 Mm
Width	77.0 Mm
Depth	40.0 Mm
Embedding depth	26.0 Mm
Projecting depth	14.5 Mm

Environment

Standards	ABNT NBR NM 60669-2-1 NMX J-508 ANCE NCh 2027/1 NCh 2027/2 IEC 60669
Product certifications	SEC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	76.358 G
Package 1 Height	4.0 Cm
Package 1 width	9.5 Cm
Package 1 Length	19.0 Cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	1.527 Kg
Package 2 Height	21.5 Cm
Package 2 width	15.8 Cm
Package 2 Length	26.5 Cm

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Product Life Status :	Commercialised
-----------------------	----------------