Product data sheet Characteristics

S3B62096

Switch, Miluz, 1 way and 2 way, 10AX, graphite





Main

Range	Miluz
Product or component type	Switch

Complementary

- Comprehensive	
Device presentation	Complete mechanism
Device mounting	Flush
Colour tint	Graphite (RAL 7016)
Type of packing	Flow-pack
Switch function	1-way + 2-way switch
Ambient air temperature for operation	-545 °C
Number of rocker	2
Local signalling	Without pilot light
Marking	1 - L 1 - 2 - L
Rated current	10 A
[Ue] rated operational voltage	250 V AC
Material	Thermoplastic ABS-UV stabilised: rocker PA66: casing PS (polystyrene): fixing frame Thermoplastic ABS-UV stabilised: cover frame
Number of modules	2 modules
Fixing mode	By screws
Connections - terminals	Screw-clamp terminals
Number of cables	2
Cable cross section	4 Mm²
Wire stripping length	12 Mm
Surface finish	Glossy Matt
AWG gauge	AWG 12
Height	115.0 Mm
Width	77.0 Mm
Depth	40.0 Mm
Embedding depth	26 Mm
Projecting depth	14.5 Mm
-	

Environment

Standards	ABNT NBR NM 60669-2-1 NMX J-508 ANCE IEC 60669
IP degree of protection	IP2x

Packing Units

. doming office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	77.1 G
Package 1 Height	4.0 Cm
Package 1 width	9.5 Cm
Package 1 Length	19.0 Cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	1.542 Kg
Package 2 Height	21.5 Cm
Package 2 width	15.8 Cm
Package 2 Length	26.5 Cm

Offer Sustainability

onor odotamability		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Product Life Status : Commercialised

