



Main

Range	Miluz
Product or component type	Switch

Complementary

Device presentation	Complete mechanism
Device mounting	Flush
Colour tint	Graphite (RAL 7016)
Type of packing	Flow-pack
Switch function	Triple 1-way
Ambient air temperature for operation	-5...45 °C
Number of rocker	3
Local signalling	Without pilot light
Marking	1 - L
Rated current	10 A
[Ue] rated operational voltage	250 V AC
Material	Thermoplastic ABS-UV stabilised: rocker PA66: casing PS (polystyrene): fixing frame Thermoplastic ABS-UV stabilised: cover frame
Number of modules	3 modules
Fixing mode	By screws
Connections - terminals	Screw-clamp terminals
Number of cables	2
Cable cross section	4 Mm ²
Wire stripping length	12 Mm
Surface finish	Glossy Matt
AWG gauge	AWG 12
Height	115.0 Mm
Width	77.0 Mm
Depth	40.0 Mm
Embedding depth	26 Mm
Projecting depth	14.5 Mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.






Environment

Standards	ABNT NBR NM 60669-2-1 NMX J-508 ANCE IEC 60669
IP degree of protection	IP2x

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	89.1 G
Package 1 Height	4.0 Cm
Package 1 width	9.5 Cm
Package 1 Length	19.0 Cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	1.782 Kg
Package 2 Height	21.5 Cm
Package 2 width	15.8 Cm
Package 2 Length	26.5 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Product Life Status : **Commercialised**