

# Product data sheet

Specifications



## Italian socket outlet, Miluz, 2P+E, 10A, 250V, graphite

S3B60226

### Main

|                           |                              |
|---------------------------|------------------------------|
| Range                     | Miluz                        |
| Product or component type | Socket-outlet<br>Cover frame |
| Fixing mode               | By screws                    |

### Complementary

|                                |                                                                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Device presentation            | Complete mechanism                                                                                                                     |
| Outlet standard description    | With earthing contact                                                                                                                  |
| Outlet poles configuration     | 2P + E                                                                                                                                 |
| Device mounting                | Flush                                                                                                                                  |
| Colour tint                    | Graphite (RAL 7016)<br>Graphite                                                                                                        |
| Outlet standard                | Italian                                                                                                                                |
| Type of packing                | Flow-pack                                                                                                                              |
| [In] rated current             | 10 A                                                                                                                                   |
| [Ue] rated operational voltage | 250 V AC                                                                                                                               |
| Material                       | ASA + PC: centre plate<br>Thermoplastic ABS-UV stabilised: cover frame<br>PS (polystyrene): fixing frame<br>PC (polycarbonate): casing |
| Surface finish                 | Glossy<br>Painted                                                                                                                      |
| Number of modules              | 1 module                                                                                                                               |
| Connections - terminals        | Screw-clamp terminals                                                                                                                  |
| Number of cables               | 2                                                                                                                                      |
| Cable cross section            | 1.5...2.5 mm²                                                                                                                          |
| Wire stripping length          | 11 mm                                                                                                                                  |
| AWG gauge                      | AWG 14                                                                                                                                 |
| Height                         | 115.0 mm                                                                                                                               |
| Width                          | 77.0 mm                                                                                                                                |
| Depth                          | 30.5 mm                                                                                                                                |
| Embedding depth                | 22.0 mm                                                                                                                                |

|                  |        |
|------------------|--------|
| Projecting depth | 8.5 mm |
|------------------|--------|

### Environment

|                         |                          |
|-------------------------|--------------------------|
| Standards               | NCh 2027/1<br>NCh 2027/2 |
| IP degree of protection | IP2x                     |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 63.4 g   |
| Package 1 Height             | 3.1 cm   |
| Package 1 width              | 9.5 cm   |
| Package 1 Length             | 19.0 cm  |
| Unit Type of Package 2       | CAR      |
| Number of Units in Package 2 | 20       |
| Package 2 Weight             | 1.267 kg |
| Package 2 Height             | 21.5 cm  |
| Package 2 width              | 15.8 cm  |
| Package 2 Length             | 26.5 cm  |

### Offer Sustainability

|                            |                                                                                                             |
|----------------------------|-------------------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                           |
| REACH free of SVHC         | Yes                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                            |
| Mercury free               | Yes                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |